

# NEW! NBT-23



*New Tank Style Acidic pH Treatment Product*  
Features a clear see through cover, easy change out pellet media bag, ABS flow baffle, low profile outlet port; wall or floor mounted.

**JJM Boiler Works, Inc.**



<b>MODEL #</b>	NBT-23
<b>RATING/MBH</b>	1 - 300 MBH
<b>FLOW RATE</b>	0 - 2.4 GPH
<b>INLET PORT SIZE/PVC</b>	.75" Socket
<b>OUTLET PORT SIZE/PVC</b>	.75" Socket
<b>MOUNTING/HORIZONTAL</b>	Floor or Wall
<b>COVER PLATE</b>	Clear Polycarbonate
<b>TANK</b>	Blue Polypropylene
<b>GASKET</b>	EPDM Flat Gasket
<b>WALL BRACKETS</b>	Steel
<b>BAFFLE PLATE</b>	ABS Plastic
<b>LOCK NUTS</b>	ABS Plastic
<b>COVER HOLD DOWN BOLT &amp; NUT/STEEL</b>	8 - 32 x .5" / 8 - 32
<b>ACTIVE INGREDIENT/ pH POWER PELLETS™</b>	Magnesium Hydroxide Pellets
<b>DIMENSIONS</b>	11.75" L x 4.74" W x 4.875" H
<b>INLET PORT HEIGHT</b>	.875" On Center
<b>OUTLET PORT HEIGHT</b>	3.0" On Center

## Current JJM Customers:

The new NBT-23 can be used in place of the JM-2, JM-2 Clear, JM-3, and JM-3 Clear. 1 SKU replaces 4 SKU's.

One Pellet Media Bag can replace the JM-2 Refill, JM-2 Clear Refill, JM-3 Refill, and JM-3 Clear Refill. 1 Refill SKU replaces 4 Refill SKU.

- Rating of 1 to 300 MBH Max.
- Flow rate of 0 to 2.4 GPH Max.
- Low outlet profile at 3" from the floor
- Low inlet profile at .875" from the floor
- No pipe union required
- PVC socket fittings standard
- One media bag per NBT-23
- Easy replacement media bag
- No need for clear inline tubes
- Clear tank cover
- Safety cover hold down bolts and nuts
- Floor or wall mounting
- Wall mounting brackets standard
- Ratings replace the JM-2, JM-2C, JM-3, and JM-3C
- Polypropylene tank 140F constant
- Polycarbonate clear cover
- Standard two-year warranty on NBT-23



Your **GREEN**  
SOLUTION

JJM Boiler Works, Inc.  
413-527-1893 | [jjmtubes@charter.net](mailto:jjmtubes@charter.net) | [www.jjmboilerworks.com](http://www.jjmboilerworks.com)  
© 2010 JJM Boiler Works, Inc.